



## HomeGuard™ Seam Tape

HomeGuard™ Seam Tape is a polypropylene sheathing tape coated with an aggressive acrylic pressure sensitive adhesive (PSA) designed for use as a closure system and vapor seal on all interior and exterior sheathing materials. HomeGuard Seam Tape exceeds most building code requirements and can be used for new construction as well as repair on all vapor barrier materials. HomeGuard Seam Tape is the highest performing, highest value product on the market today. Available in white and 1 7/8" x 165'

### Product Construction



————— Biaxially oriented polypropylene (BOPP)  
 ————— Acrylic adhesive

### Features & Benefits

- High performance sheathing tape installs and performs well over a wide temperature range
- Excellent vapor barrier tape on polyethylene film
- Performs well as a seam tape on extruded foam products such as Styrofoam® and Foamular®
- Applies to all major housewraps including Tyvek® and Typar®
- Great for use as a sealing tape on DensGlass Gold® and other sheathing brands

### Technical Data for HomeGuard™ seam tape

Properties	Typical Value	Typical Value (Metric)	Test Method
Product Thickness	3.0 mils	0.08 mm	PSTC-133
Peel Adhesion			
to stainless steel	45 oz/in	12.5 N/25 mm	PSTC-101
to polyethylene	16 oz/in	4.5 N/25 mm	PSTC-101
to Tyvek	25 oz/in	6.9 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	20 lb/in	90.4 N/25 mm	PSTC-131
Elongation	130%	130%	PSTC-131
WVTR	0.061 perms		ASTM E96
Service Temperature	-40 to 185°F	-40 to 85°C	



**HomeGuard  
Building Products  
Inc.**

6797 Thoreau Lane  
 Baltimore, OH 43105  
 Office: 616.846.0804  
 Fax: 866.337.4016  
[www.homeguardhousewrap.com](http://www.homeguardhousewrap.com)