



Ox Engineered Products  
p. 1.800.345.8881  
f. 248.289.9955  
oxep.com



## **OX Shield** SEAM TAPE by OX

Ox Shield Tape is a polyethylene tape made up of polyethylene laminated synthetic fabric backing. Ox Shield Tape is designed to work with Ox Shield™ Surface Protection by providing excellent adhesion while leaving little to no adhesive residue on the Ox Shield™ panel. This makes it the ideal product for protecting new or existing concrete, wood, tile, stone, linoleum, epoxy and most other surfaces on the jobsite.

### **Usage**

For use with OX Shield™  
Surface Protection

### **Applications:**

Masking of rougher surfaces,  
temporary holding of interior  
construction materials, and  
temporary seam tape for Ox  
Shield Surface Protection  
Panels

### **Available:**

Red 2 3/8" x 165'

## Attributes

- For use with Ox Shield Surface Protection
- Low residue adhesive formula
- Hand Tearable
- Low profile so contours to various surfaces

## Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.



## Product Construction

Backing	PE laminated synthetic backing
Adhesive	Synthetic Resin PSA

## Technical Data

Total Thickness	4 mil
Tensile	17 lbs./in.
Adhesion	25 oz./in.
Application temperature	10° F (12°C) - 95° F (35°C)
Service temperature	-40°F (-40°C) -176° F (80°C)